



technical specifications

| | |
|-------------------------------------|--|
| Product Name | Velour Excel |
| Product Description | Fibre Bonded |
| Pile Yarn Description | 85% Polypropylene 15% Nylon |
| Tile Dimensions | 50cm x 50cm |
| Pile Weight | 1200g/m ² +/-10% |
| Total Weight | 4900g/m ² +/-10% |
| Total Thickness | 10mm +/-10% |
| Backing Description | Accummen™, 75% recycled |
| Wear Classification | Heavy Contract |
| Flammability | Euroclass Bfl-s1 |
| Thermal Resistance | Tog Rating 0.84; ISO 8302: 0.10 m ² K/W |
| Castor Chair Rating | BS EN 985 Pass - suitable for continuous use |
| Body Voltage Test | BS ISO 6356:2000 <2kV |
| Colour Fastness To Light | BS EN ISO 105 - B02 Minimum grade 6 |
| Colour Fastness To Shampoo | BS 1006:UK-TB: 1990 Minimum Grade 4 |
| Sound Absorption Coefficient | BS EN 354:2003 |
| Reduction in Impact Noise | BS EN 140-8: Part 8: 1998 21dB |
| Reduction in Impact Noise at 1000hz | BS EN 140-8: Part 8: 1998 32.1dB |
| Number of Tiles per Box | 16 (4m ²) |



For best results we recommend




Quarter Turn




07
0338-CPD-1005
EN 14041:2004








This floor covering was made with renewable electricity



Environmental Profiles Scheme
Certificate Number ENP353



Certificate Number FM01440
BS EN ISO 9001:2008



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+ (very low-emission) to C (high-emission)

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications
For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 OAN
United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE
Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards.
Orders are subject to Burmatex terms and conditions of sale.
See: www.burmatex.co.uk

LRV values for **velour excel**

| Product code | Product colour name | CIE Y | CIE L |
|---------------------|----------------------------|--------------|--------------|
| 6022 | assyrian jade | 9.90 | 37.66 |
| 6023 | iceni blue | 2.56 | 18.18 |
| 6028 | saxon blue | 3.08 | 20.34 |
| 6036 | phoenician green | 2.73 | 18.95 |
| 6040 | armenian grey | 4.54 | 25.38 |
| 6045 | trojan green | 5.14 | 27.14 |
| 6050 | norman steel | 7.30 | 32.48 |
| 6055 | dorian azure | 5.42 | 27.9 |
| 6056 | spartan mauve | 7.00 | 31.81 |
| 6060 | barona blue | 3.32 | 21.27 |
| 6061 | skydancer | 7.73 | 33.41 |
| 6062 | red lake | 3.03 | 20.15 |
| 6066 | navajo mauve | 2.71 | 18.82 |
| 6070 | yakama slate | 1.82 | 14.49 |
| 6081 | bavarian blue | 5.95 | 29.29 |
| 6082 | mayan sky | 6.83 | 31.43 |
| 6083 | norse green | 4.10 | 24.01 |
| 6090 | persian purple | 2.68 | 18.73 |